



F-Theta JENar™ Lens Series  
Large Scan Fields – JENar™ 160-1030...1080-170




Parameters	JENar™ 160-1030...1080-170 Compact F-Theta lens for large scan fields
Focal length:	160 mm
Wavelength:	1030...1080 nm
Scan field ( X x Y ); Ø:	(120 mm x 120 mm); 170 mm
Diagonal scan angle:	60°
Back working distance:	178.4 mm
Flange focus distance:	194.1 mm
Input beam Ø 1/e²:	10 mm
Focus size Ø 1/e²:	31 µm
a1:	13 mm
a2:	42.5 mm
Telecentricity (only F-Theta   with scanner):	17.1°   17.2°
Group delay dispersion (GDD)*:	934 fs²
LIDT coating pulsed; CW*:	5.0 J/cm² * (τ/[ns]) ^ 0.30; 5.0 MW/cm²
LIDT system pulsed; CW*:	5.0 J/cm² * (τ/[ns]) ^ 0.30; 5.0 MW/cm²
Weight:	0.383 kg
Order Number::	017700-019-26


Spot properties



Specifications  
JENar™ 160-1030...1080-170



Definition of geometrical parameters



JENar®: Registered in EU, CN, JP, SG, US | F-Theta: Registered Design in EU, CN, KR, JP, SG, IN, HK, TW

The data given are nominal values for the specified application parameters. Jenoptik provides Zemax® BlackBox files for simulating application results for customized parameters (e.g. wavelength, scanner geometry, beam diameter, ...).  
Back working distance, Flange focus distance, and focal length vary by ± 1.5 % due to manufacturing variances.

It is our policy to constantly improve the design and specifications. Accordingly, the details represented herein cannot be regarded as final and binding.